# SCART to PAL

# **Converter** ID# 045



**Operation Manual** 



### Introduction

This unit will convert from a scart input to a SVHS or composite output. It is ideal for digital satellite receivers or DVD players that do not have a suitable S-Video output to feed a video projector or picture signal to a surround sound system.

#### Features

• Converts scart RGB signal from a satellite receiver or other video sources to SVHS or Composite video for recording or further connecting to TV.

• It performs the functions of a converter plus video stabilizer.

# **Operating Functions and Controls Front Panel**



**1. Power ON/OFF indicator-** This will illuminate when the power has been turned on.

## **Rear Panel**





	<ol> <li>DC 7.5V Center Negative: This is where you connect your power supply.</li> <li>Video output- This is the video output port. An RCA connector is used for composite video to connect the port to the output device.</li> <li>S-Video output- This is the S-Video output port. An S-Video jack for Y/C output is used to connect the port to the output device.</li> <li>Audio output pair (L + R)/2 sets- Two sets of audio output ports.</li> <li>Scart RGB input- This is the input port. Connect the input port to your Scart output device (sky satellite receiver or other video sources) using your input Scart connector.</li> </ol>
Connection and	
Installation	<ul> <li>The AC adaptor power unit should not be plugged into a wall outlet until all connections are complete.</li> <li>Using your connector cable connect the RGB input port (Number 5 on the rear panel) to the scart output such as a sky satellite receiver or another type of video source.</li> <li>Using your connector cable connect the output port (Number 2/3/4 on the rear panel) to the output device (TV or VCR).</li> <li>Once all connections are complete please connect the power supply provided to the power socket</li> </ul>
Specifications	

Input system	PAL
Output system	PAL
Connection terminals	Scart input: 1
	Video output: 1
	S-Video output. 1
	Audio output (R+L): 2
AC adaptor	Input: 230V/50 Hz
	Output: DC 7.5 V 500mA Center Negative
Dimensions	236 (W) x 130 (D) x 45 (H)
Weight	0.5 Kg
Accessory	Video cable, AC adaptor

